



SBC Self-Aligning Ball Bearing 调心球轴承

基本尺寸(mm)				轴承型号		额定载荷(N)		极限转速(rpm)		重量(kg)
Principal dimensions				Bearing No.		Basic load ratings		Speed ratings		weight
d	D	B	r(min)	圆柱孔	圆锥孔	dynamic (Cr)	static (Cor)	脂 (grease)	油(oil)	
5	19	6	0.3	135	-	2510	480	28000	34000	0.009
6	19	6	0.3	126	-	2510	480	28000	34000	0.009
7	22	7	0.3	127	-	2650	560	26000	36000	0.014
8	22	7	0.3	108	-	2650	560	26000	36000	0.014
9	26	8	0.6	129	-	3900	815	24000	28000	0.021
10	30	9	0.6	1200	1200K	5480	1200	24000	28000	0.035
	30	14	0.6	2200	2200K	7120	1580	24000	28000	0.05
	35	11	0.6	1300	1300K	7220	1620	20000	24000	0.06
	35	17	0.6	2300	2300K	11000	2450	18000	22000	0.09
12	32	10	0.6	1201	1201K	5550	1250	22000	26000	0.042
	32	14	0.6	2201	2201K	8800	1800	22000	26000	0.053
	37	12	1	1301	1301K	9420	2120	18000	22000	0.07
	37	17	1	2301	2301K	12500	2720	17000	22000	0.095
15	35	11	0.6	1202	1202K	7480	1750	18000	22000	0.051
	35	14	0.6	2202	2202K	7650	1800	18000	22000	0.06
	42	13	1	1302	1302K	9500	2280	16000	20000	0.1
	42	17	1	2302	2302K	12000	2880	14000	18000	0.11
17	40	12	0.6	1203	1203K	7900	2020	16000	20000	0.076
	40	16	0.6	2203	2203K	9000	2450	16000	20000	0.09
	47	14	1	1303	1303K	12500	3180	14000	17000	0.14
	47	19	1	2303	2303K	14500	3580	13000	16000	0.17
20	47	14	1	1204	1204K	9950	2650	14000	17000	0.12
	47	18	1	22.4	2204K	12500	3280	14000	17000	0.15
	52	15	1.1	1304	1304K	12500	3380	12000	15000	0.17
	52	21	1.1	2304	2304K	17800	4750	11000	14000	0.22
25	52	15	1	1205	1205K	12000	3330	12000	14000	0.14
	52	18	1	2205	2205K	12500	3400	12000	14000	0.19
	62	17	1.1	1305	1305K	17800	5050	10000	13000	0.26
	62	24	1.1	2305	2305K	24500	6480	9500	12000	0.35
30	62	16	1	1206	1206K	15800	4700	10000	12000	0.23
	62	20	1	2206	2206K	15200	4600	10000	12000	0.26
	72	19	1.1	1306	1306K	21500	6280	8500	11000	0.4
	72	27	1.1	2306	2306K	31500	8680	8000	10000	0.5
35	72	17	1.1	1207	1207K	15800	5080	8500	10000	0.32
	72	23	1.1	2207	2207K	21800	6650	8500	10000	0.44
	80	21	1.5	1307	1307K	25000	7950	7500	9500	0.54



SBC Self-Aligning Ball Bearing 调心球轴承

基本尺寸(mm)				轴承型号		额定载荷(N)		极限转速(rpm)		重量(kg)
Principal dimensions				Bearing No.		Basic load ratings		Speed ratings		weight
d	D	B	r(min)	圆柱孔	圆锥孔	dynamic (Cr)	static (Cor)	脂 (grease)	油(oil)	
	80	31	1.5	2307	2307K	39200	11000	7100	9000	0.68
40	80	18	1.1	1208	1208K	19200	6400	7500	9000	0.41
	80	23	1.1	2208	2208K	22500	7380	7500	9000	0.53
	90	23	1.5	1308	1308K	29500	9500	6700	8500	0.71
	90	33	1.5	2308	2308K	44800	13200	6300	8000	0.93
45	85	19	1.1	1209	1209K	21800	7320	7100	8500	0.49
	85	23	1.1	2209	2209K	23200	8000	7100	8500	0.55
	100	25	1.5	1309	1309K	38000	12800	6000	7500	0.96
	100	36	1.5	2309	2309K	55000	16200	5600	7100	1.25
50	90	20	1.1	1210	1210K	22800	8080	6300	8000	0.54
	90	23	1.1	2210	2210K	23200	8450	6300	8000	0.68
	110	27	2	1310	1310K	43200	14200	5600	6700	1.21
	110	40	2	2310	2310K	64500	19800	5000	6300	1.64
55	100	21	1.5	1211	1211K	26800	10000	6000	7100	0.72
	100	25	1.5	2211	2211K	26800	9950	6000	7100	0.81
	120	29	2	1311	1311K	51500	18200	5000	6300	1.58
	120	43	2	2311	2311K	75200	23500	4800	6000	2.1
60	110	22	1.5	1212	1212K	30200	11500	5300	6300	0.9
	110	28	1.5	2212	2212K	34000	12500	5300	6300	1.1
	130	31	2.1	1312	1312K	57200	20800	4500	5600	1.96
	130	46	2.1	2312	2312K	86800	27500	4300	5300	2.6
65	120	23	1.5	1213	1213K	31000	12500	4800	6000	0.92
	120	31	1.5	2213	2213K	43500	16200	4800	6000	1.5
	140	33	2.1	1313	1313K	61800	22800	4300	5300	2.39
	140	48	2.1	2313	2313K	96000	32500	3800	4800	3.2
70	125	24	1.5	1214	1214K	34500	13500	4800	5600	1.29
	125	24	1.5	1214	1214K	34500	13500	4800	5600	1.345
	125	31	1.5	2214	2214K	44000	17000	4500	5600	1.62
	150	35	2.1	1314	1314K	74500	27500	4000	5000	3
	150	51	2.1	2314	2314K	110000	37500	3600	4500	3.9
75	130	25	1.5	1215	1215K	38800	15200	4300	5300	1.35
	130	31	1.5	2215	2215K	44200	18000	4300	5300	1.72
	160	37	2.1	1315	1315K	79000	29800	3800	4500	3.6
	160	55	2.1	2315	2315K	122000	42800	3400	4300	4.7
80	140	26	2	1216	1216K	39500	16800	4000	5000	1.65



SBC Self-Aligning Ball Bearing 调心球轴承

基本尺寸(mm)				轴承型号		额定载荷(N)		极限转速(rpm)		重量(kg)
Principal dimensions				Bearing No.		Basic load ratings		Speed ratings		weight
d	D	B	r(min)	圆柱孔	圆锥孔	dynamic (Cr)	static (Cor)	脂 (grease)	油(oil)	
	170	39	2.1	1316	1316K	88500	32800	3600	4300	4.2
	170	58	2.1	2316	2316K	128000	45500	3200	4000	5.7
85	150	28	2	1217	1217K	48800	20500	3800	4500	2.1
	150	28	2	2217	2217K	47800	19500	3800	4500	2.24
	180	41	3	1317	1317K	97800	37800	3400	4000	5
	180	60	3	2317	1317K	140000	51000	3000	3800	6.7
90	160	30	2	1218	1218K	56500	23200	3600	4300	2.5
	160	40	2	2218	2218K	70000	28500	3600	4300	3.22
	190	43	3	1318	1318K	115000	44500	3200	3800	6
	190	64	3	2318	2318K	142000	57200	2800	3600	7.9
95	170	32	2.1	1219	1219K	63500	27000	3400	4000	3
	170	43	2.1	2219	2219K	82800	33800	3400	4000	4.2
	200	45	3	1319	1319K	132000	50800	3000	3600	7
	200	67	3	2319	2319K	162000	64200	2800	3400	9.2
100	180	34	2.1	1220	1220K	68500	29200	3200	3800	3.7
	180	46	2.1	2220	2220K	97200	40500	3200	3800	5
	215	47	3	1320	1320K	142000	47200	2800	3400	8.64
	215	73	3	2320	2320K	192000	78500	2400	3200	12.4
105	190	36	2.1	1221	1221K	74000	32200	3000	3600	4.4
	190	50	2.1	2221	2221K	10000	40000	3000	3600	6.1
	225	49	3	1321	1321K	152000	64500	2600	3200	9.55
	225	77	3	2321	2321K	218000	92500	2400	3000	18.485